



Status of the COMET experiment

Manabu MORITSU (KEK)


On behalf of the COMET Collaboration

20th Workshop on Neutrinos from Accelerators (NUFACT2018)

13th Aug., 2018, Virginia Tech, Blacksburg

Lepton flavor violation (LFV)

Neutrino Oscillation



Charged Lepton Flavor Violation

We already know that lepton flavor is no longer conserved

✓ neutrino oscillation, non-zero m_ν

The conservation law was just an empirical law

✓ without any symmetry behind

However,

**in the charged lepton sector,
LFV has never been observed yet...**

$$\frac{\Gamma(\mu \rightarrow e\gamma)}{\Gamma(\mu \rightarrow e\nu\nu)} \propto \left| \sum_i \frac{m_i^2}{m_W^2} U_{\mu i}^* U_{ei} \right|^2 \sim 0(10^{-54})$$

small mass ratio of neutrino to weak boson

Since the SM contribution is negligibly small,

observation of the CLFV indicates a clear evidence of **New Physics**.

Charged LFV in muons


- $\mu^+ \rightarrow e^+ \gamma$
- $\mu^+ \rightarrow e^+ e^+ e^-$
- $\mu^- N \rightarrow e^- N$ (μ -e conversion)

Effective Lagrangian


$$\mathcal{L} = \underbrace{\frac{1}{1+\kappa} \frac{m_\mu}{\Lambda^2} \bar{\mu}_R \sigma^{\mu\nu} e_L F_{\mu\nu}}_{\text{Photonic}} + \underbrace{\frac{\kappa}{1+\kappa} \frac{1}{\Lambda^2} (\bar{\mu}_L \gamma^\mu e_L)(\bar{q}_L \gamma_\mu q_L)}_{\text{4-fermion}}$$

New Physics contributions


Photonic (dipole) term



4-fermion (contact) term



New Physics scale




- ✓ Different measurements are complementary.
- ✓ μ -e conversion is sensitive to both contributions.

Photonic \leftarrow \rightarrow 4-fermion


Muon-to-electron conversion

Fate of muonic atom

1s state in a muonic atom



nuclear muon capture (61% in Al)



μ-e conversion




single mono-energetic electron

$$E_{\mu e} = m_\mu - B_\mu - E_{\text{rec}} = 104.97 \text{ MeV for Al}$$

Current upper limit

SINDRUM-II, EPJ C47, 337 (2006)

$$\text{Br}(\mu^- \text{ Au} \rightarrow e^- \text{ Au}) < 7 \times 10^{-13}$$



Background rejection

- ① **Decay-in-orbit** → **Detector**
- ② **Beam-related prompt BG** → **Beam**
- ③ **Cosmic-ray induced** → **Veto**



Background rejection (1)

① Decay-in-orbit


→ Detector resolution

Intrinsic physics background

Muon decay in orbit



Simulation Signal and DIO ($\text{BR} = 3 \times 10^{-15}$)



Required momentum resolution

$$\Delta p < 200 \text{ keV/c}$$


for 105 MeV/c electrons

Background rejection (2)

② Beam-related prompt BG → Pulsed Beam

muon beam is contaminated by a lot of pions, and the momentum is spreading in a wide range.

- Radiative pion capture, $\pi^- (A,Z) \rightarrow (A,Z-1) \gamma, \gamma \rightarrow e^+ e^-$
 - Muon decay in flight, $p_\mu > 75 \text{ MeV}/c$
 - Anti-proton induced, etc.
- } correlated with beam timing



Cf.) $\tau_\mu(\text{Al}) = 0.9 \mu\text{sec}$

✓ Long muon beam line

- reduce π contami.

✓ Pulsed beam

- prompt vs. delayed

➡ Delayed-timing measurement


Lifetime of the muonic atom should be comparable to the pulse interval

Background rejection (2)

② Beam-related prompt BG → Pulsed Beam

muon beam is contaminated by a lot of pions, and the momentum is spreading in a wide range.

- Radiative pion capture, $\pi^- (A,Z) \rightarrow (A,Z-1) \gamma, \gamma \rightarrow e^+ e^-$
 - Muon decay in flight, $p_\mu > 75 \text{ MeV}/c$
 - Anti-proton induced, etc.
- } correlated with beam timing



✓ Long muon beam line

- reduce π contami.

✓ Pulsed beam

- prompt vs. delayed

➡ Delayed-timing measurement



✓ Extinction factor $< 10^{-10}$

$$R_{\text{ext}} = \frac{\# \text{ of protons in between pulses}}{\# \text{ of protons in pulses}}$$

Leaked protons are dangerous to make the beam BG in the timing window.

Background rejection (3)

③ Cosmic-ray induced → Veto



- Cosmic rays may create 105-MeV electrons that come into a detector and make trigger.
- To avoid these CR induced BG, detector region have to be covered by veto counters.
- Required performance: **CRV inefficiency $\sim 10^{-4}$**
- CR background \propto data taking time (\rightarrow shorter running time with higher beam intensity is better)




The COMET Experiment

Collaboration Meeting @ Osaka, 2018/Jan




~200 collaborators,
41 institutes, 17 countries

Accelerator





Proton beam for COMET

Cf.) Requirement $< 10^{-10}$






Extinction @ J-PARC MR Abort



- COMET dedicated operation
 - Energy: 8 GeV
 - Pulsed beam: 1.17-μsec interval
 - 3.2 kW for Phase-I
 - 56 kW for Phase-II
- Obtained Extinction
 - = $10^{-12} \sim 10^{-11}$ @ FX abort
 - Good enough for COMET

Beam line

- New beam line & experimental hall were constructed.
- **Bunched Slow Extraction (BSX)**
 - keeping bunch structure to realize the pulsed beam.



High-intensity muon source

Powerful muon source is mandatory !!


To achieve 10^{-17} sensitivity,

$\sim 10^{11}$ muons/sec



(with 10^7 sec running time.)

- ▶ Long production target
- ▶ Capture solenoid
 - Backward generated pion \rightarrow muon
- ▶ Curved Transport solenoid
 - Vertical drift \rightarrow Momentum & charge selection

Capture solenoid




Transport solenoid



Demonstrated at MuSIC

COMET Phase-I




★ Physics measurement → CyDet

- μ -e conversion search, SES: 3×10^{-15} ($\times 100$ improve), 150 days running

★ Beam measurement → StrECAL

- to understand beam quality and background (PID, momentum, timing)

COMET Phase-II




- SES: 2×10^{-17} ($\times 10,000$ improve)
- Beam: 56 kW
- 1 year running



Recent Status

Beam line construction

View from here



2017/Sep.

Concrete Wall
(Oct. 5)

(will become)
Concrete Wall
(Nov. 17)

Stage for
magnet
power

high-p BL

COMET BL




2018/Jan.

High-p


COMET

Beam line wall construction was completed.

Solenoid magnet status



- **Capture solenoid:**
 - Coil winding & cold mass assembly in progress. Cryostat design ongoing.
- **Transport solenoid:**
 - Installed and ready for cryogenic test
- **Bridge & Detector solenoids:**
 - DS coil ready. Cryostat design in progress.
- **Cryogenic System:**
 - Refrigerator test completed. Helium transfer tube in production



CyDet system

Detector for μ -e search in Phase-I

■ CDC (Cylindrical Drift Chamber)




- electron tracking in 1 T
- $\Delta p = 200 \text{ keV}/c$ (for $p = 105 \text{ MeV}/c$)
- Low-mass chamber
 - He:i-C₄H₁₀ (90:10)
 - 0.5-mm CFRP inner wall
 - Al field wire, 126 μm , 4986
 - Au-W sense wire, 25 μm , 14562
- Alternating all stereo layer
 - 20 layers, $\pm 64 \sim 75 \text{ mrad}$

■ CTH (Cylindrical Trigger Hodoscopes)

- Scintillator & Acrylic Cherenkov
- Finemesh PMT readout
- 4-fold coincidence trigger

■ Stopping Target

- Al target consists of 17 discs
- 100-mm radius, 0.2-mm thickness, 50-mm spacing.




CyDet status





CDC cosmic-ray test is ongoing in KEK.
Good performance was obtained.

(a) Event Display




(a)

residual distribution for testlayer10




All 120 CDC FE boards were fabricated,
and QA was finished in IHEP.




High-level track trigger

- Software-level algorithm was already established.
- can reduce background hits into 1/20 while retaining 99% of signals.



CTH structure prototype
is under construction.




StrECAL system

Detector for beam measurement in Phase-I,
and μ -e search in Phase-II

■ Straw Tube Tracker

- Operational in vacuum in 1 T
- $\Delta p = 150 \sim 200 \text{ keV}/c$ (for $p = 105 \text{ MeV}/c$)
- Straw tube
 - $20 \mu\text{m}$ thick, 9.75 mm diameter for Phase-I
 - $12 \mu\text{m}$ thick, 5 mm diameter for Phase-II
- 5 stations ($xx'yy' \times 5$)
- Ar:C₂H₆ (50:50)




■ Electron Calorimeter

- 1,920 LYSO crystals
 - $2 \times 2 \times 12 \text{ cm}$ (10.5 radiation length)
- $\Delta E/E = 5\%$ (for $E = 105 \text{ MeV}$)
- 40-ns decay time
- APD readout



Straw Tracker prototype




ECAL prototype


StrECAL status



Straw tube production for Phase-I was completed.





Thermal study of FE in gas manifold was carried out.
Straw station assembly will start soon.




Buying procedure of ~ 500 LYSO for Phase-I is ongoing.

StrECAL Beam Test @ 2017




Straw:
position resolution $< 150 \mu\text{m}$




ECAL:
 $\Delta E/E < 4.4\% @ 105 \text{ MeV}$

8 GeV test & Extinction measurement

8-GeV operation & extinction measurement were done at J-PARC in Jan.-Feb., 2018.



- Campaign was successfully carried out.
- Extinction was measured by both FX & SX.
- ✓ **First trial of 8 GeV Bunched SX.**



See Hajime Nishiguchi's talk on Friday



Sensitivity and Background

Sensitivity

Event selection	Value
Online event selection efficiency	0.9
DAQ efficiency	0.9
Track finding efficiency	0.99
Geometrical acceptance + Track quality cuts	0.18
Momentum window (ϵ_{mom})	0.93 $103.6 < p_e < 106.0 \text{ MeV/c}$
Timing window (ϵ_{time})	0.3 $700 < t_e < 1170 \text{ ns}$
Total	0.041

@ Phase-I

$$B(\mu^- + \text{Al} \rightarrow e^- + \text{Al}) = N_\mu \cdot f_{\text{cap}} \cdot f_{\text{gnd}} \cdot A_{\mu-e}$$


= 3×10^{-15}

Number of muons stopped inside targets

Fraction of μ -e conversion to the ground state = 0.9

Fraction of muons to be captured by Al target = 0.61

$N_\mu = 1.5 \times 10^{16} \rightarrow \text{150 days by 3.2 kW}$



@ Phase-II

1 year by 56 kW

+ Tungsten production target
+ 180° Transport Solenoid
+ Electron Spec. Solenoid


S.E.S

= 2×10^{-17}

Background estimation

Type	Background	Estimated events
Physics	Muon decay in orbit	0.01
	Radiative muon capture	0.0019
	Neutron emission after muon capture	< 0.001
	Charged particle emission after muon capture	< 0.001
Prompt Beam	* Beam electrons	
	* Muon decay in flight	
	* Pion decay in flight	
	* Other beam particles	
	All (*) Combined	≤ 0.0038
Delayed Beam	Radiative pion capture	0.0028
	Neutrons	~ 10 ⁻⁹
	Beam electrons	~ 0
	Muon decay in flight	~ 0
	Pion decay in flight	~ 0
Delayed Beam	Radiative pion capture	~ 0
	Anti-proton induced backgrounds	0.0012
Others	Cosmic rays [†]	< 0.01
Total		0.032

[†] This estimate is currently limited by computing resources.



$$103.6 < p_e < 106.0 \text{ MeV/c}$$

Assuming

$$R_{\text{ext}} = 3 \times 10^{-11}$$

$$700 < \tau_e < 1170 \text{ ns}$$

@ Phase-I

BG is small enough

@ Phase-II

BG is still less than 1 by simulation

to be confirmed by Phase-I Beam Measurement

Summary & Prospects



- ▶ COMET aims to search for μ -e conversion with sensitivity of 3×10^{-15} / 2×10^{-17} at Phase-I / II.
- ▶ Detector & beam line preparation is intensively in progress.
- ▶ Detector will be ready in 2019 for Phase-I, and commissioning will start soon after completing the beam-line construction.
- ▶ Phase-II study is also in progress. We are able to optimize the Phase-II parameters based on the coming Phase-I results.